

VACUUM PROCESSING APPARATUS AND OPERATING METHOD THEREFOR

09390621-040793

5
5
10
15
20
25
30
35
40
2

~~This application is a Continuation application of Serial No. 08/882,731, filed June 26, 1997, which is a Divisional application of Serial No. 08/593,870, filed January 30, 1996, which is a Continuing application of Serial No. 08/443,039, filed May 17, 1995, which is a Divisional application of Serial No. 08/302,443, filed September 9, 1994, which is a Continuing application of Serial No. 08/096,256, filed July 26, 1993, which is a Continuing application of Serial No. 07/751,951, filed August 29, 1991.~~

BACKGROUND OF THE INVENTION

Field of the Invention

This invention relates to a vacuum processing apparatus and operating method therefor. More specifically, the present invention relates to a vacuum processing apparatus having vacuum processing chambers the inside of which must be cleaned, and its operating method.

Description of the Prior Art

In a vacuum processing apparatus such as a dry etching apparatus, a CVD apparatus or a sputtering apparatus, a predetermined number of substrates to be treated are stored as one unit (which is generally referred to as a "lot") in a substrate cassette and are loaded in the apparatus. The substrates after being processed are likewise stored in the same unit in the substrate cassette and are recovered. This is an ordinary method of operating these apparatuses to improve the productivity.

In such a vacuum processing apparatus described above, particularly in an apparatus which utilizes a reaction by an active gas, as typified by a dry etching apparatus and a CVD apparatus, reaction products adhere to and are deposited on a vacuum processing chamber with the progress of processing. For this reason, problems such as degradation of vacuum performance, the increase of dust, the drop of the levels of optical monitoring signals occur. To solve these problems, conventionally the insides of the vacuum processing chambers are cleaned periodically. Cleaning operations include so-called "wet cleaning" which is wiping-off of the adhering

5

10

20

25

30

5

25

30

35

substrates between the second storage means and the vacuum processing chambers before and after dry-cleaning of the vacuum processing chambers.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Fig. 1 is a plan view of a dry etching apparatus as an embodiment of a vacuum processing apparatus in accordance with the present invention; and

Fig. 2 is a vertical sectional view taken along line 1 - 1 of Fig. 1.

10 DESCRIPTION OF THE PREFERRED EMBODIMENTS

As substrates to be processed are processed in a vacuum processing apparatus, reaction products adhere to and are deposited in vacuum processing chambers. The reaction products adhering to and deposited in the vacuum processing chambers are removed by disposing dummy wafers inside the vacuum processing chambers and by conducting dry-cleaning. To carry out dry cleaning, the timings of dry cleaning of the vacuum processing chambers are determined and during or after the processing of a predetermined number of substrates to be processed, dummy substrates are conveyed by substrate conveyor means from dummy substrate storage means disposed in the air atmosphere together with processed substrate storage means, and are then disposed inside the vacuum processing chambers. After the dummy substrates are thus disposed, a plasma is generated inside each of the vacuum processing chambers to execute dry-cleaning inside the vacuum processing chamber. After dry-cleaning inside the vacuum processing chambers is completed, the dummy substrates are returned from the vacuum processing chambers to the dummy substrate storage means by the substrate conveyor means. In this manner, a preliminary vacuum chamber and an exclusive transfer mechanism both necessary in prior art techniques become unnecessary,

5

and the apparatus structure gets simplified. The dummy substrates used for the dry-cleaning and the substrates to be processed do not co-exist inside the same chamber, so that contamination of substrates to be processed due to dust and remaining gas is prevented and a high production yield can be achieved.

Hereinafter, an embodiment of the present invention will be explained with reference to Figs. 1 and 2.

10 Figs. 1 and 2 show a vacuum processing apparatus of the present invention which is, in this case, a dry-etching apparatus for etching wafers, i.e., substrates to be processed by plasma.

Cassette tables 2a to 2c are disposed in an L-shape in this case in positions such that they can be loaded into and unloaded from the apparatus without changing their positions and postures. In other words, the cassettes 1a to 1c are fixed always in predetermined positions on a substantially horizontal plane, while the cassette tables 2a and 2b are disposed adjacent to and in parallel with each other on one of the sides of the L-shape. The cassette table 2c is disposed on the other side of the L-shape. The cassettes 1a and 1b are for storing unprocessed wafers and for recovering the processed wafers. They can store a plurality (usually 25) of wafers 20 as the substrates to be treated. The cassette 1c in this case is for storing the dummy wafers for effecting dry-cleaning using plasma (hereinafter referred to as "plasma-cleaning") and recovering the dummy wafers after plasma-cleaning. It can store a plurality of (usually twenty-five pieces) dummy wafers 30.

A load lock chamber 5 and unload lock chamber 35 6 are so disposed as to face the cassette tables 2a

6

5

20

35

7

5

10

15

30

8

chambers 11a, 11b, 11c by the conveyors 13 and 14, and are etched. The etched wafers are stored in their original positions inside the cassette 1a by the conveyors 14 and 13. In this case, from the start to the end of the operation, without changing the position and posture of the cassettes, the unprocessed wafers are taken out from the cassettes and are returned in their original positions where the wafers have been stored, and are stored there. In this manner, the apparatus can easily cope with automation of the production line, contamination of the wafers due to dust can be reduced and high production efficiency and high production yield can thus be accomplished.

As etching is repeated, the reaction products adhere to and are deposited on the inner wall of the etching chambers 11a to 11c. Therefore, the original state must be recovered by removing the adhering matters by plasma cleaning. The controller 19 judges the timing of this plasma cleaning. In this case, a portion through which the plasma light passes is provided in each of the etching chambers 11a to 11c. The sensor 18 measures the intensity of the plasma light passing through this portion and when the measured value reaches a predetermined one, the start timing of plasma cleaning is judged. Alternatively, the timing of plasma cleaning may be judged by counting the number of wafers processed in each etching chamber by the controller 19 and judging the timing when this value reaches a predetermined value. The actual timing of plasma cleaning that is carried out may be during a processing of a predetermined number of wafers in the cassette 1a or 1b, after the processing of all the wafers 20 in a cassette is completed and before the processing of wafers in the

Plasma cleaning is carried out in the following sequence. In this case, the explanation will be given about a case where the etching chambers 11a to 11c are subjected to plasma cleaning by using three dummy wafers 30 among the dummy wafers 30 (twenty-five dummy wafers are stored in this case) stored in the cassette 1c.

Dummy wafers 30 which are stored in the cassette 1c and are not used yet or can be used because the number of times of use for plasma cleaning is below a predetermined one are drawn by the conveyor 13. At this time, dummy wafers 30 stored in any position in the cassette 1c may be used but in this case, the position numbers of the dummy wafers in the cassette and their number of times of use are stored in the controller 19, and accordingly dummy wafers having smaller numbers of times of use are drawn preferentially. Then, the dummy wafers 30 are loaded in the load lock chamber 5 disposed on the opposite side to the cassette 1a by the conveyor 13 through the gate valve 12a in the same way as the transfer at the time of etching of wafers 20. After the gate valve 12a is closed, the load lock chamber 5 is evacuated to a predetermined pressure by the vacuum exhaust device 3 and then the gate valves 12b and 15a are opened. The dummy wafers 30 are transferred by the conveyor 14 from the load lock chamber 5 to the etching chamber 11a through the transfer chamber 16 and are placed on the sample table 8a. After the gate valve 15a is closed, plasma cleaning is carried out in the etching chamber 11a in which the dummy wafers 30 are disposed, under a predetermined condition.

In the interim, the gate valves 12a, 12b are closed and the pressure of the load lock chamber 5 is

returned to the atmospheric pressure by the gas introduction device 4. Next, the gate valve 12a is opened and the second dummy wafer 30 is loaded in the load lock chamber 5 by the conveyor 13 in the same way as the first dummy wafer 30, and evacuation is effected again by the evacuating device 3 to a predetermined pressure after closing the gate valve 12a. Thereafter, the gate valves 12b and 15b are opened and the second dummy wafer 30 is transferred from the load lock chamber 5 to the etching chamber 11b through the transfer chamber 16 by the conveyor 14. Plasma cleaning is started after the gate valve 15b is closed.

In the interim, the third dummy wafer 30 is transferred into the etching chamber 11c in the same way as the second dummy wafer 30 and plasma cleaning is carried out.

After plasma cleaning is completed in the etching chamber 11a in which the first dummy wafer 20 is placed, the gate valves 15a and 12c are opened. The used dummy wafer 30 is transferred from the etching chamber 11a to the unload lock chamber 6 by the conveyor 14. Then, the gate valve 12c is closed. After the pressure of the unload lock chamber 6 is returned to the atmospheric pressure by the gas introduction device 4, the gate valve 12d is opened. The used dummy wafer 30 transferred to the unload lock chamber 6 is taken out in the air by the conveyor 13 through the gate valve 12d and is returned to its original position in the cassette 1c in which it is stored at the start.

When plasma cleaning of the etching chambers 11b and 11c is completed, the second and third dummy wafers 20 are returned to their original positions in the cassette 1c.

In this way, the used dummy wafers 30 are returned to their original positions in the cassette 1c and the dummy wafers 30 are always stocked in the cassette 1c. When all the dummy wafers 30 in the cassette 1c are used for plasma cleaning or when the numbers of times of use of the wafers 30 reach the predetermined ones after the repetition of use, the dummy wafers 30 are replaced as a whole together with the cassette 1c. The timing of this replacement of the cassette is managed by the controller 19 and the replacement is instructed to the host control apparatus for controlling the line transfer robot or to the operator.

Although the explanation given above deals with the case where the etching chambers 11a to 11c are continuously plasma-cleaned by the use of three dummy wafers 30 among the dummy wafers 30 in the cassette 1c, other processing methods may be employed, as well.

For example, the etching chambers 11a to 11c are sequentially plasma-cleaned by the use of one dummy wafer 30. In the case of such plasma cleaning, unprocessed wafers 20 can be etched in etching chambers other than the one subjected to plasma cleaning, and plasma cleaning can thus be carried out without interrupting etching.

If the processing chambers are different, for example, there are an etching chamber, a post-processing chamber and a film-formation chamber, and wafers are sequentially processed while passing through each of these processing chambers, each of the processing chambers can be subjected appropriately to plasma cleaning by sending dummy wafers 30 during the processing of the wafers 20 which are stored in the cassette 1a or 2a and drawn and sent sequentially, by passing merely the dummy wafers 30 through the

002200634 0007590

processing chambers for which plasma cleaning is not necessary, and by executing plasma cleaning only when the dummy wafers 30 reach the processing chambers which need plasma cleaning.

5 According to the embodiment described above, the cassette storing the dummy wafers and the cassettes storing the wafers to be processed are disposed together in the air, the dummy wafers are loaded from the cassette into the apparatus by the same conveyor as the conveyor for transferring the wafers, at the
10 time of cleaning, and the used dummy wafers are returned to their original positions in the cassette. In this way, a mechanism for conducting exclusively plasma cleaning need not be provided, and the
15 construction of the apparatus can be simplified. It is not necessary to handle plasma cleaning as a particular processing sequence, but the plasma cleaning can be incorporated in an ordinary etching processing and can be carried out efficiently in a
20 series of operations.

The dummy wafers used for plasma cleaning are returned to their original positions in the cassette placed in the air. Accordingly, the used dummy wafers and the wafers before and after processing do not
25 exist mixedly in the vacuum chamber, so that contamination of wafers due to dust and remaining gas does not occur unlike conventional apparatuses.

The used dummy wafers are returned to their original positions in the cassette and the numbers of
30 times of their use is managed. Accordingly, it is possible to prevent the confusion of the used dummy wafers with the unused dummy wafers and the confusion of the dummy wafers having small numbers of times of use with the dummy wafers having large numbers of
35 times of use. For these reasons, the dummy wafers can

00300681 090799

13

be used effectively without any problem when plasma cleaning is carried out.

Furthermore, in accordance with the present invention, the apparatus can have a plurality of processing chambers and can transfer wafers and dummy wafers by the same conveyor. Since plasma cleaning can be carried out by managing the timing of cleaning of each processing chamber by the controller, the cleaning cycle can be set arbitrarily, dry cleaning can be carried out without interrupting the flow of the processing, the processing can be efficiently made and the productivity can be improved.

As described above, according to the present invention, there are effects that the construction of the apparatus is simple, the substrates to be processed are free from contamination and the production yield is high.

00200584 000799
002000 T8902200